



TEGAM

Product Status

Prepared on:
29-Sept-2025

Model	Product Description	EOL	Best Replacement PN:
1000092	Calorimeter System 10kW, AC Primary Chiller	N	
1000092-318	Calorimeter System 10kW, 3-1/8 Connector, AC, Primary Chiller	N	
1000121	Calorimeter System 10kW, WC Primary Chiller	N	
1000108A	HPC-250, High Power Calibration System	N	
102-1000	Splitter Support Bracket for F1109, F1116 & F1119	Y	No Replacement
102-1000H	Splitter Support Bracket for F1109H, F1116H & F1119H	Y	No Replacement
110-404	Replacement Lead Test Set for Model 110A	Y	No Replacement
1104	Utility Belt Carrying Case (Leather) for 110A, 120, 122, & 125	Y	No Replacement
1130-910-01	Torque Wrench, 8mm, 5 in-lbs, SMA to 1585-1000	N	
1130-911-01	Torque Wrench, 3/4", 12 in-lbs, N (Standard Nut)	N	
1130-912-01	Torque Wrench, 13/16", 14 in-lbs, (Special 13/16" Nut on M1130A, M1125, M1110)	N	
1130-913-02	Attenuator, 20 dB, Type N Coax (M) to (F), with Data	N	
1135-913-02	Attenuator, 20 dB, 3.5 mm Coax (M) to (F), with Data	N	
1204A	Utility/Lineman Magnetic Carrying Case (Cordura) for 110A, 120, 122 & 125	Y	No Replacement
121-404	Replacement Test Lead Set for Models 120, 122 & 125	Y	No Replacement
122-910-01	Probe Extender Kit for 110A, 122 & 125	Y	No Replacement
12501	Alligator Clip Adapters for 110A, 120, 122 & 125	Y	No Replacement
12502	Universal Adapter Kit for 110A, 120, 122 & 125	Y	No Replacement
1312	Attenuation Measurement System - 30MHz, 50MHz, 1GHz	Y	No Replacement
1314	High-Power RF Calorimeter w/ Chiller, 250W	N	
1316	High-Power RF Calorimeter, 10 kW	N	
13162	Heavy Duty Ground Stake for the R1L-C, 1 Piece	Y	No Replacement
13162/4	Heavy Duty Ground Stakes for the R1L-C, Set of 4	Y	No Replacement
1320A	High Power RF Switch Controller	N	
1321A	RF Low Pass Filter Bank - Generic	N	
1321A-011	RF Low Pass Filter Bank - 250W	N	
1321A-002	RF Low Pass Filter Bank - 250W	N	
1321A-003	RF Low Pass Filter Bank - 250W	N	
1321A-004	RF Low Pass Filter Bank - 250W	N	
1322A	High Power RF Switch Network - 250W	N	
13325	Replacement Kit for 17503 Terminals	SR	
1372A	AC Ratio Transformer Calibrator, Automated, Turnkey	N	
1372B	AC Ratio Transformer Calibrator, Automated, (1372A w/o DT-72)	N	
138-645A	RF Measurement Accessory Kit	N	
138-645-1	Attenuator, 30dB, Type N Coax (M) to (F), with Data	N	
138-645-2	Attenuator, 30dB, 3.5 mm Coax (M) to (F), with Data	N	
138-645-5	Adapter, DC to 18 GHz, N-type (M) to 3.5 mm (F), with Data	N	
138-645-6	Adapter, DC to 18 GHz, N-type (F) to 3.5 mm (M), with Data	N	
138-652	Cable, 1806 to Power Standard	N	

Model	Product Description	EOL	Best Replacement PN:
1505A	Microwave Terminating Power Standard, 9 kHz – 18 GHz Transport Case Included	N	
1500-910	Transport Case for 15XXA RF Power Standard	N	
1510A	Microwave Terminating Power Standard, 10 MHz – 50 GHz Transport Case Included	N	
1510-911-01	Adapter, DC to 40 GHz 2.4 mm (F) to 2.92 mm (M)	N	
1510-912-01	Adapter, DC to 26.5 GHz 2.4 mm (F) to 3.5 mm (M)	N	
1583-3	GPIO/IEEE-488 Cable, 1 Meter Long	N	
1583-6	GPIO/IEEE-488 Cable, 2 Meters Long	N	
1583-9	GPIO/IEEE-488 Cable, 3 Meters Long	N	
1585-1000	Test Cable with SMA Straight Plug Connectors, DC to 18 GHz, 3'	N	
1585-1003	Test Cable with SMA Straight Plug Connectors, DC to 18 GHz, 1'	N	
1585-1006	Test Cable with Type N Straight Plug Connectors, DC to 18 GHz, 3'	N	
1585-1008	Low Loss RF Cable, 26.5 GHz, 3.5 mm (M) Connectors, 3'	N	
1585-1009	Low Loss RF Cable, 40 GHz, 2.92 mm (M) Connectors, 3'	N	
1750	High-Speed Microohmmeter (not CE certified)	Y	710A
1750/220	High-speed microohmmeter; 220VAC (not CE certified)	Y	710A
1750/5.3	High Speed Microohmmeter with Choice of 17501 (Kelvin Klip) or 17502 (Spade Lug) Test Leads, Version 5.3 Firmware (not CE cert.)	Y	710A
17501	Kelvin Klip Leads for 1740 & 1750, 3'	SR	
17501-5	Kelvin Klip Leads for 1740 & 1750, 5'	SR	
17502	Spade Lug Leads for 1740 & 1750, 3'	SR	
17502-5	Spade Lug Leads for 1740 & 1750, 5'	SR	
17503	Sorting Fixture for 1740 & 1750	SR	
17505	Male Connector & Strain Relief for 1740 & 1750	SR	
17506-5	Cable, 1740 & 1750 to Bare Wire Termination, 5'	SR	
17506-8	Cable, 1740 & 1750 to Bare Wire Termination, 8'	SR	
17507	Large Kelvin Klip Lead Set, 2.5 m	SR	
1750C	High-Speed Microohmmeter (not CE certified)	Y	710A
1820B	RF Mount Temperature Controller	N	
1830A	RF Thermistor Power Meter	N	
1830-910	Single Unit Rack Mount Kit, 1830A, F113XB & 25XXA Series	N	
1830-911	Dual Unit Rack Mount Kit, 1830A, F113XB & 25XXA Series	N	
2340 (TG-2340)	Precision Power Amplifier, High Voltage, Single Channel	Y	TREK 2100HF
2348	Precision Power Amplifier, High Current, Single Channel	Y	TREK 2100HF
2350	Precision Power Amplifier, High Voltage, Dual Channel	Y	TREK 2100HF
2505A	Microwave Calibration Standard, Feedthrough, 9 kHz to 18 GHz	N	
2500-910	Transport Case for 1830A, F113X & 25XXA	N	
2510A	Microwave Calibration Standard, Feedthrough, 10 MHz-50 GHz	N	
2510-910-01	Torque Wrench, 8 mm, 8 in-lbs, for 3.5 mm, 2.92 mm and 2.4 mm	N	
2510-911-01	Adapter, 2.4 mm coax (M) to 2.92 mm (F) with Data	N	
2510-912-01	Adapter, 2.4 mm coax (M) to 3.5 mm (F) with Data	N	
2510-913-01	Attenuator, 30 dB, 2.4 mm Coax (M) to (F) with Data	N	
2510-913-20	Attenuator, 20 dB, 2.4 mm Coax (M) to (F), with Data	N	
2510-914-01	Adaptor, Coax, 2.4mm (M) to N (F), with Data	N	

Model	Product Description	EOL	Best Replacement PN:
252	LCR Meter, 1 kHz	Y	No Replacement
252/SP2596	LCR Meter, 1 kHz, Battery Powered	Y	No Replacement
252/SP2596/220	LCR Meter, 1 kHz, Battery Powered, 220V Line Power	Y	No Replacement
2601A	High Power RF Transfer Standard, 250 kHz to 1000 MHz, Transport Case Included	N	
2602A	High Power RF Transfer Standard, 750 MHz to 3500 MHz, Transport Case Included	N	
260X-910	Transport Case for High-Power RF Transfer Standards 2601A & 2602A	N	
2818A	RF Transfer Standard, 9kHz to 18GHz, USB	N	
2850A	RF Transfer Standard, 10MHz to 50GHz, USB	N	
43374	Dust Cover for 252, 253, 254	Y	No Replacement
47422	2 Wire Tweezer Tip Replacement Kit - 12 Tips, 2 Screws & 1 Allen Wrench for SKT-3, SKT-5, SKT/252-5 & SKT/1750-5	SR	
47423	4 Wire Tweezer Tip Replacement Kit - 12 Tips, 2 Screws & 1 Allen Wrench for SKT-3, SKT-5, SKT/252-5 & SKT/1750-5	SR	
47424	4 Wire Angled Tweezer Tip Replacement Kit - 12 Tips, 2 Screws & 1 Allen Wrench for SKT-3, SKT-5, SKT/252-5 & SKT/1750-5	SR	
47454	Kelvin Klips, 5 Terminal, for 3525 and 3550, 5'	Y	No Replacement
5540A-CAL-0001	Calibration to the Input Port. 13.56 MHz, 3W to 5000W	N	
5540A-CAL-0002	Calibration to the Input Port. 2.0-30.0MHz, 5W to 250W	N	
5540A-CAL-0003	Calibration to the Input Port. 2MHz, 3W to 5000W	N	
5540A-CAL-0004	Calibration to the Input Port. 60MHz, 3W to 5000W	N	
5540A-CAL-0005	Calibration to the Input Port. 380kHz, 3W to 5000W	N	
5540A-CAL-0006	Calibration to the Input Port. 1MHz, 3W to 5000W	N	
5540A-CAL-0007	Calibration to the Input Port. 27.12MHz, 3W to 2000W	N	
5540A-CAL-0008	Calibration to the Input Port. 0.20MHz, 3W to 2500W	N	
5540A-CAL-0009	Calibration to the Input Port. 0.40MHz, 3W to 5000W	N	
5540A-CAL-0010	Calibration to the Input Port. 40.68MHz, 3W to 5000W	N	
5540A-CAL-1011	Calibration to the Input Port. 570kHz, 3W to 2000W	N	
5540A-CAL-1013	Calibration to the Input Port. 350kHz, 3W to 2000W	N	
5540A-CAL-1014	Calibration to the Input Port. 12.88MHz, 3W to 2000W	N	
5540A-CAL-1015	Calibration to the Input Port. 415kHz, 3W to 2000W	N	
5540A-7/16F-7/16F	5540A with Two Female 7/16 Connectors	N	
5540A-7/16F-7/16M	5540A with One Female 7/16 Connector and One Male 7/16 Connector	N	
5540A-7/16F-HNM	5540A with One Female 7/16 Connector and One Male HN Connector	N	
5540A-7/16F-NF	5540A with one Female 7/16 Connector and One Female N Connector	N	
5540A-HNF-7/16F	5540A with a Female HN Connector and a Female 7/16 Connector	N	
5540A-HNF-HNF	5540A with Two Female HN Connectors	N	
5540A-HNF-HNM	5540A with One Female HN Connector and One Male HN Connector	N	
5540A-HNF-NF	5540A with One Female HN Connector and One Female N Connector	N	
5540A-HNM-HNF	5540A with One Male HN Connector and One Female HN Connector	N	
5540A-LCF-LCM	5540A with One Female LC Connector and One Male LC Connector	N	
5540A-NF-NF	5540A with Two Female N Connectors	N	
5540A-NF-HNF	5540A with One Female N Connector and One Female HN Connector	N	

Model	Product Description	EOL	Best Replacement PN:
5540A-NF-HNM	5540A with One Female N Connector and One Male HN Connector	N	
5540A-NF-NM	5540A with One Female N Connector and One Male N Connector	N	
5540A-NM-NM	5540A with Two Male N Connectors	N	
5541A-7/16F-7/16F	5540A with Two Female 7/16 Connectors	N	
5541A-HNF-HNF	5541A with Two Female HN Connectors	N	
5541A-NF-NM	5541A with One Female N Coonector and One Male N Connector	N	
5541A-QDSUF-QDSUIM	5541A with QDSU Female/Male Connectors and Interlock	N	
6501/MC-1201	Case with Foam, R1L-C Accessory Kit	SR	
700-910	Tilt Stand/Strap Hanger/Magnet (Factory Installed)	N	
700-911	Hard Carry Case	N	
700-912	Tilt Stand/Strap Hanger/Magnet (User Installed)	N	
700-915	Sure Grip Cover fits 700 Series Bond Meters & 900 Series Digital Thermometers	N	
710A	Handheld Bond Meter	N	
710A-BK-KIT	Bond Meter Kit includes 710A, BKDP-M2, BKP-M2, BKP-B(2), 700-911 Carry Case	N	
720A	Handheld Bond Meter, Intrinsically Safe	N	
720A-BK-KIT	I.S. Bond Meter Kit includes 720A, BKP-M2S (2), BKP-B(2), 700-911 Carry Case	N	
720A-KIT	I.S. Bond Meter Kit includes 720A, BKP-M2S, BKEP-M2S, BKP-K, 720-915, 720-916 Carry Case	N	
730A	Handheld Bond Meter, Wireless Datalogging	N	
720-910	Tilt Stand, Carrying Strap, Intrinsically Safe (factory installed)	N	
720-911	Carrying Case, Spark-proof, 7XX Series	N	
720-912	Tilt Stand, Carrying Strap, Intrinsically Safe (user installed)	N	
720-915	Sure Grip Cover, Intrinsic Safe, 720A	N	
720-916	Carrying Case, Spark-proof, 7XX Series (part of 720-kit)	N	
740532	Single Rackmount Kit, Center - 5-1/4" Height - Center Mount for Models 2340, 2348, 2350, 2375, 2411A, 2411B, 2414A, 2414B, 2711A, 2714A	Y	No Replacement
740949	BNC to High-Voltage BNC Cable, 3', for 2340/2350	SR	
8000	Case, RF Mount Transport, F/M11xx	N	
80010	AC Adapter/Battery Charger for Model 840A Through 855	Y	No Replacement
8012	6 Input Switch Box T/C, Type K	SR	
80141	Cable, Type K, Extension, (M) to (F), 3'	SR	
8022	6 Input Switch Box T/C ,Type J	SR	
8052	6 Input Switch Box T/C, Type T	SR	
865	Thermistor Thermometer °F; (not CE certified)	Y	911B
866	Thermistor Thermometer °C (not CE certified)	Y	911B
868	Platinum RTD Thermometer °F (not CE certified)	Y	911B
869	Platinum RTD Thermometer °C (not CE certified)	Y	911B
8737A	Temperature Probe, Type K, Griddle	N	
900-913	Belt Clip for 700 & 900 Series (Factory Installed)	N	
900-914	Belt Clip for 700 & 900 Series (User Installed)	N	
911B	Thermocouple Thermometer, Single Input °C & °F (K, J, T & E)	N	
911-910	Tilt Stand/Magnet/Hanger for 911X, 912X, 931X, 932X (Factory Installed)	N	

Model	Product Description	EOL	Best Replacement PN:
911-911	Foam-Filled Hard Carry Case for 911X, 912X, 931X, 932X	N	
911-912	Tilt Stand/Magnet/Hanger for 911X, 912X, 931X, 932X (User Installed)	N	
912B	Thermocouple Thermometer, Dual Input °C & °F (K, J, T & E)	N	
921B	Intrinsically Safe Thermocouple Thermometer, Single Input, °C & °F (K, J, T, E, B, N, R & S)	N	
922B	Intrinsically Safe Thermocouple Thermometer, Dual Input, °C & °F (K, J, T, E, B, N, R & S)	N	
931B	Data Thermometer, Bluetooth® Wireless, Single Input °C & °F (K, J, T, E, B, N, R & S)	N	
932B	Data Thermometer, Bluetooth® Wireless, Dual Input °C & °F (K, J, T, E, B, N, R & S)	N	
940A	J,K,T,E Thermocouple Calibrator + mV	N	
940-912E	Calibration Adapter Cable, Type E Mini T/C Connector to Spade Lugs, 3', with Mini T/C Male to Standard Female Adapter & Standard T/C Connector	N	
940-912J	Calibration Adapter Cable, Type J Mini T/C Connector to Spade Lugs, 3', with Mini T/C Male to Standard Female Adapter & Standard T/C Connector	N	
940-912K	Calibration Adapter Cable, Type K Mini T/C Connector to Spade Lugs, 3', with Mini T/C Male to Standard Female Adapter & Standard T/C Connector	N	
940-912N	Calibration Adapter Cable, Type N Mini T/C Connector to Spade Lugs, 3', with Mini T/C Male to Standard Female Adapter & Standard T/C Connector	N	
940-912R/S	Calibration Adapter Cable, Type R/S Mini T/C Connector to Spade Lugs, 3', with Mini T/C Male to Standard Female Adapter & Standard T/C Connector	N	
940-912T	Calibration Adapter Cable, Type T Mini T/C Connector to Spade Lugs, 3', with Mini T/C Male to Standard Female Adapter & Standard T/C Connector	N	
940-912U	Calibration Adapter Cable, Type U Mini T/C Connector to Spade Lugs, 3', with Mini T/C Male to Standard Female Adapter & Standard T/C Connector	N	
940-913	Alligator Calibration Cable Kit, T/C Types J/K/T/E, with 4 Alligator Clip Calibration Cables & Type K Wire Probe in Foam-Filled Hard Carry Case	N	
945A	14 Thermocouple Calibrator + mV	N	
945-2750	AMS2750E Cal Option	N	
948A	Wireless Datalogging Thermocouple Calibrator; 14 TCs	N	
1000027	Filter, Thermistor Mount, Common-Mode	N	
1000042	Two Bay Rack Enclosure	N	
1000043	1830A with Cables, 5 Year Extended Warranty, Military Manual NSN: 6625-01-587-7130 For Sale to Qualified Military End-Users and Suppliers Only	N	
1000078	Data Thermometer Kit w/ Model 931B Bluetooth® Wireless, Single Input, °C & °F (K, J, T, E, B, N, R & S) Thermometer w/ ISO 17025 Calibration, 9T604MTC03 Type T Hypodermic Probe, 911-912 Tilt Stand/Magnet/Hanger in Foam-Filled Hard Carrying Case	N	
1000079	912B Thermometer and Case	N	
9J603MTC05	Temperature Probe, Type J, Immersion, MTC Connector, 5"	N	
9K002MTC36	Temperature Probe, Type K, Wire, MTC Connector, 36"	N	
9K002MTC72	Temperature Probe, Type K, Wire, MTC Connector, 72"	N	
9K104MTC18	Temperature Probe, Type K, T-Handle, Penetration, MTC Connector, 18"	N	
9K104MTC30	Temperature Probe, Type K, T-Handle, Penetration, MTC Connector, 30"	N	
9K104MTC35	Temperature Probe, Type K, T-Handle, Penetration, 35"	N	
9K105MTC12	Temperature Probe, Type K, T-Handle, Surface, 12"	N	
9K603MTC05	Temperature Probe, Type K, Immersion, MTC Connector, 5"	N	

Model	Product Description	EOL	Best Replacement PN:
9K603MTC12	Temperature Probe, Type K, Immersion, MTC Connector, 12"	N	
9K604MTC04	Temperature Probe, Type K, Penetration, MTC Connector, 4"	N	
9K604MTC18	Temperature Probe, Type K, Penetration, MTC Connector, 18"	N	
9K604MTC30	Temperature Probe, Type K, Penetration, MTC Connector, 30"	N	
9K605MTC08	Temperature Probe, Type K, Surface, MTC Connector, 8"	N	
9K606MTC08	Temperature Probe, Type K, Air/Gas, MTC Connector, 8"	N	
9K607MTC03	Temperature Probe, Type K, Hypodermic, MTC Connector, 3"	N	
9K607MTC04	Temperature Probe, Type K, Hypodermic, MTC Connector, 4"	N	
9T002MTC36	Temperature Probe, Type T, Wire, MTC Connector, 36"	N	
9T002MTC72	Temperature Priobe, Type T, Wire, MTC Connector, 72"	N	
9T104MTC18	Temperature Probe, Type T, T-Handle, Penetration, MTC Connector, 18"	N	
9T104MTC30	Temperature Probe, Type T, T-Handle, Penetration, MTC Connector, 30"	N	
9T104MTC36	Temperature Probe, Type T, T-Handle, Penetration, MTC Connector, 36"	N	
9T307MTC04	Temperature Probe, Type T, Detachable, Hypodermic, MTC Connector, 4"	N	
9T603MTC05	Temperature Probe, Type T, Immersion, MTC Connector, 5"	N	
9T603MTC12	Temperature Probe, Type T, Immersion, MTC Connector, 12"	N	
9T604MTC04	Temperature Probe, Type T, Penetration, MTC Connector, 4"	N	
9T604MTC18	Temperature Probe, Type T, Penetration, MTC Connector, 18"	N	
9T604MTC30	Temperature Probe, Type T, Penetration, MTC Connector, 30"	N	
9T605MTC06	Temperature Probe, Type T, Surface, MTC Connector, 6"	N	
9T606MTC04	Temperature Probe, Type T, Air/Gas, MTC Connector, 4"	N	
9T606MTC08	Temperature Probe, Type T, Air/Gas, MTC Connector, 8"	N	
9T607MTC03	Temperature Probe, Type T, Hypodermic, MTC Connector, 3"	N	
9T607MTC04	Temperature Probe, Type T, Hypodermic, MTC Connector, 4"	N	
9T797MTCPVC36	Temperature Probe, Type T, Fast Response Hypodermic, 3" 36" FEP Cable	N	
9X002PHN36	Temperature Probe, Thermistor, Wire, 1/4" Phono Connector, 36"	N	
9X104PHN18	Temperature Probe, Thermistor, T Handle, Penetration, 1/4" Phono Connector, 18"	N	
9X104PHN30	Temperature Probe, Thermistor, T Handle, Penetration, 1/4" Phono Connector, 30"	N	
9X104PHN36	Temperature Probe, Thermistor, T Handle, Penetration, 1/4" Phono Connector, 36"	N	
9X603PHN04	Temperature Probe, Thermistor, Immersion, 1/4" Phono Connector, 4"	N	
9X604PHN04	Temperature Probe, Thermistor, Penetration, 1/4" Phono Connector, 4"	N	
9X604PHN18	Temperature Probe, Thermistor, Penetration, 1/4" Phono Connector, 18"	N	
9X604PHN30	Temperature Probe, Thermistor, Penetration, 1/4" Phono Connector, 30"	N	
9X605PHN04	Temperature Probe, Thermistor, Surface, 1/4" Phono Connector, 4"	N	
9X606PHN04	Temperature Probe, Thermistor, Air/Gas, 1/4" Phono Connector, 4"	N	
9Y603TA408	Temperature Probe, RTD, Immersion, TA4 Connector, 8"	N	
9Y605TA406	Temperature Probe, RTD, Surface, TA4 Connector, 6"	N	
9Y606TA408	Temperature Probe, RTD, Air/Gas, TA4 Connector, 8"	N	
BCP-10-A	Pin Kit, 8 Pins per Pack, 30° Pointed Tip	N	
BCP-10-B	Pin Kit, 8 Pins per Pack, Plunger Flat Tip	N	
BCP-10-C	Pin Kit, 8 Pins per Pack, Large Rounded Tip (.090 in)	N	
BCP-10-D	Pin Kit, 8 Pins per Pack, Concave Tip	N	

Model	Product Description	EOL	Best Replacement PN:
BCP-10-F	Pin Kit, 8 Pins per Pack, 40° Chisel Tip	N	
BKDP-M2	Big Kelvin Display Probe, 700 Series	N	
BKEP-M2	Big Kelvin Extended Probe, 700 Series	N	
BKEP-M2S	Big Kelvin Extended Probe, Intrinsically Safe, 700 Series	N	
BKP/1750-5	Big Kelvin Probe, 1750 Connector	SR	
BKP-10	Big Kelvin Probe, Banana Connector	N	
BKP-B	Pin Kit, Spear Tip, 4 Pins per Pack	N	
BKP-F	Pin Kit, Flat Tip, 4 Pins per Pack	N	
BKP-H	Pin Kit, Serrated Tip, 4 Pins per Pack	N	
BKP-J	Pin Kit, Rounded Tip, 4 Pins per Pack	N	
BKP-K	Pin Kit, Narrow Profile, Rounded Tip, 4 Pins per Pack	N	
BKP-M2	Big Kelvin Probe, 700 Series	N	
BKP-M2S	Big Kelvin Probe, 700 Series, Intrinsically Safe	N	
CA-191	Cable Assembly, RTD Jack to Alligator Clip	Y	No Replacement
CA-6-48	Cable, Sensor, 1830A to 8478B and 478A Sensor, 48"	N	
CA-7-15	Cable, 1830A to F/M Mounts, 15"	N	
CA-7-48	Cable, 1830A to F/M Mounts, 48"	N	
CA-9-48	Cable, 1830A to Unterminated Ends, 48"	N	
CA-10-15	Cable, 1830A and 1806A to Large Heater, 15"	N	
CA-10-48	Cable, 1830A and 1806A to Large Heater, 48"	N	
CA-11-15	Cable, 1830A and 1806A to Small Heater, 15"	N	
CA-11-48	Cable, 1830A and 1806A to Small Heater, 48"	N	
CA-14-2M	Cable, USB A/A 2M	N	
CA-162-36	Kelvin Klips for 252, 253, 254, 3'	SR	
CA-162-72	Kelvin Klips for 252, 253, 254, 6'	SR	
CA-20-24	Calibration Cable for the 1830A with Spade Lugs, 24"	N	
CA-20-48	Calibration Cable for the 1830A with Spade Lugs, 48"	N	
CA-21-15	Cable, Voltage Bias and Heater, 1830A to 15XX/25XX, 15"	N	
CA-21-48	Cable, Voltage Bias and Heater, 1830A to 15XX/25XX, 48"	N	
CA-22-36	Cable, RS232C, DB9 to DB9 M/F, 1740 & 1750	SR	
CA-23-12	Low Loss RF Cable, 50GHz, 2.4 mm (M) Connectors, 12", for PMX	N	
CA-23-36	Low Loss RF Cable, 50GHz, 2.4 mm (M) Connectors, 36", for PMX	N	
CA-27-48	Cable, 1805 and 1806 to Large Heater, 48"	N	
CA-28-48	Cable, 1806A to 15XXA/25XXA	N	
CA-29-48	Cable, 1806 to 15XXA/25XXA	N	
DT72B	AC Ratio Standard, 7 Decades	N	
EW-1372B-5	5 Year Extended Warranty 1372B	N	
GPIB-USB-HS	GPIB to USB adaptor	N	
HKC-100	Large Kelvin Test Lead Set	SR	
HPC-SW	High Power RF Calibration System Software	N	
HTP-100	Kelvin Pistol Grip Probes, Stainless Steel Pins	Y	HTP-101A
HTP-101A	Kelvin Pistol Grip Probes for R1L-E2A	SR	
HTRH-D	High-Temperature RH/Temperature Transmitter, 4-20 mA, Duct Mount	Y	No Replacement
HTRH-W	High-Temperature RH/Temperature Transmitter, 4-20 mA, Wall Mount	Y	No Replacement
HUB-103	USB HUB	N	

Model	Product Description	EOL	Best Replacement PN:
IS9J113MTC48	Temperature Probe, Intrinsically Safe, Type J, T-handle, Immersion (Tapered), 48"	N	
IS9K104MTC36	Temperature Probe, Intrinsically Safe, Type K, T-handle, Penetration, 36"	N	
IS9K104MTC48	Temperature Probe, Intrinsically Safe, Type K, T-handle, Penetration, 48"	N	
IS9K603MTC06	Temperature Probe, Intrinsic Safe, Type K, Immersion, Non-Tapered, 6"	N	
IS9K605MTC06	Temperature Probe, Intrinsic Safe, Type K, Surface, 6"	N	
IS9K606MTC06	Temperature Probe, Intrinsic Safe, Type K, Air/Gas, 6"	N	
IS9K613MTC06	Temperature Probe, Intrinsic Safe, Type K, Immersion, Tapered, 6"	N	
IS9T603MTC06	Temperature Probe, Intrinsic Safe, Type T, Immersion, Non-Tapered, 6"	N	
IS9T605MTC06	Temperature Probe, Intrinsic Safe, Type T, Surface, 6"	N	
IS9T606MTC06	Temperature Probe, Intrinsic Safe, Type T, Air/Gas, 6"	N	
IS9T613MTC06	Temperature Probe, Intrinsic Safe, Type T, Immersion, Tapered, 6"	N	
IS9T797MTCPVC36	Intrinsic Safe Temperature Probe, Type T, Fast Response Hypodermic 3" 36" FEP Cable	N	
KAK-04	Kelvin Alligator Set	SR	
KC-M2	Kelvin Klip, 700 Series, 2m	N	
KC-M2S	Kelvin Klip, 700 Series, 2m, Intrinsically Safe	N	
KC-M5	Kelvin Klip, 700 Series, 5m	N	
KC-M5S	Kelvin Klip, 700 Series, 5m, Intrinsically Safe	N	
KK100	Kelvin Klip Replacement Kit for CA-162-36, 17501, 47454 & 27838	SR	
KK-BAND	Kelvin Klip Bands, Quantity 20 Per Pack	SR	
KTL-100	Kelvin Klip, for R1L-B, R1L-BR, R1L-D1, 7'	SR	
KTL-910	Kelvin Klip Replacement Kit for KTL-100	SR	
M11XX-STAND	3" Riser for M1125A, M1130A & M1135A	Y	No Replacement
MCDP-M2	Miniature Coaxial Kelvin Display Probe, 700 Series	N	
MCP/1750-5	Miniature Coaxial Probe, 1750 Connector	SR	
MCP-6	Miniature Coaxial Probe, Banana Connector	SR	
MCP-A	Replacement Pins for the MCP Series Probe	SR	
MCP-M2	Miniature Coaxial Probe, with M12 Connector, 700 Series	N	
MCP-M2S	Miniature Coaxial Probe, with M12 Connector, 700 Series, Intrinsically Safe	N	
MKDP-M2	Miniature Kelvin Display Probe, 700 Series	N	
MKP/1750-5	Miniature Kelvin Probe, 1750 Connector	SR	
MKP-6	Miniature Kelvin Probe, Banana Connector	SR	
MKP-B	Spear Tip Pin Kit, 4 Per Pack	N	
MKP-F	Flat Tip Pin Kit, 4 Per Pack	N	
MKP-H	Serrated Tip Pin Kit, 4 Per Pack	N	
MKP-J	Round Tip Pin Kit, 4 Per Pack	N	
MKP-LM	Serrated Rotating Tip Pin Kit, 4 Per Pack	N	
MKP-M2	Miniature Coaxial Probe, 700 Series	N	
MKP-M2S	Miniature Coaxial Probe, 700 Series, Intrinsically Safe	N	
OPT-11	Rack Mount for DSRB, DSRS, M-1011A & M-1012A	N	
OPT-700-17025	17025 Calibration Option 700 Bondmeter Series	N	
OPT-900-17025	17025 Calibration Option 900 Thermometer Series	N	
PDU-21	AC Line Power Distribution Unit	N	

Model	Product Description	EOL	Best Replacement PN:
PMX18-012	RF Power Sensor Calibration System 9 kHz to 18 GHz, Consists of: (1) 1830A (1) 2505A (1 each) CA-21-15, CA-14-2M	N	
PMX18-CS-02-01	Complete 9kHz to 18GHz Power Sensor Calibration System including Signal Generator, VNA, 2505A, 1830A, and accessories	N	
PMX50-002	RF Power Sensor Calibration System 10 MHz to 50 GHz, Consists of: (1) 1830A (1) 2510A (1 each) CA-21-15 and CA-14-2M	N	
PMX50-014	RF Power Sensor Calibration System 9 kHz to 50 GHz, Consists of: (2) 1830A (1) 2505A (1) 2510A (2 each) CA-21-15, CA-14-2M	N	
PR-850	Probe, Surface Resistance	SR	
PS-CAL	PS-Cal Power Sensor Calibration Software	N	
PS-CAL-UPDATE	PS-Cal Power Sensor Calibration Software Upgrade	N	
PS-CAL-EUP-5	Extend PS-Cal Update Plan by 4 Years	N	
PT-P900W	Label Printer, Power Sensors	N	
R1L-BI	Microohm and Bond Meter, Bench Top 10 $\mu\Omega$ to 20 Ω , Includes KTL-100 Kelvin Klips (not CE certified)	Y	710A
R1L-BIR	Microohm and Bond Meter, Portable 10 $\mu\Omega$ to 20 Ω , No Leads Included (not CE certified)	Y	710A-BK-KIT
R1L-BIR1	Microohm and Bond Meter, Portable 10 $\mu\Omega$ to 20 Ω , with 4-Wire Push-Pin & Alligator Clip Probes (not CE certified)	Y	710A-BK-KIT
R1LC-070	Wire Lead/Spool Assembly for R1L-C Accessory Kit (M616), 250'	Y	No Replacement
R1LC-075	Wire Lead/Wrap Assembly for R1L-C Accessory Kit (M662), 75'	Y	No Replacement
R1LC-910	Complete Accessory Kit for the R1L-C in Case	Y	No Replacement
R1L-D1	Microohm and RTD Meter, Low Current, 10 $\mu\Omega$ to 2 k Ω , No Leads Included (not CE certified)	Y	710A-BK-KIT
R1L-E2A	Intrinsically Safe Microohm and Bond Meter, 10 $\mu\Omega$ to 20 Ω , Includes Standard "HTP-101A" Probes	Y	720A-BK-KIT
R1L-E2A/SKP-8	Intrinsically Safe Microohm and Bond Meter, 10 $\mu\Omega$ to 20 Ω , Includes "SKP-8" Probes	Y	720A-BK-KIT
R1M-910-850	Surface Resistance Probes for the Model R1M-A (not CE certified)	Y	No Replacement
R1M-A	Megohmmeter, Portable 1 M Ω to 200 G Ω , 3%, 500V, 3.5 Digit (no CE)	Y	No Replacement
R1M-AR+850	Megohmmeter, Portable, 1 M Ω to 200 G Ω , 500V, 3.5 Digit, Includes R1M-910-850 Probes (not CE certified)	Y	No Replacement
R1M-B	Megohmmeter, Handheld, 1M Ω to 200M Ω , 3%, 500V, 3.5 Digit; no CE	Y	No Replacement
RDP-10V	Stainless Steel Duct RH/Temperature Transmitter and Probe, 0-10V	Y	No Replacement
RDP-20C	Stainless Steel Duct RH/Temperature Transmitter and Probe, 4-20 mA	Y	No Replacement
RH-CAL	RH Calibration Kit	Y	No Replacement

Model	Product Description	EOL	Best Replacement PN:
SDK-93X	Software Developers Kit for 931B, 932B	N	
SKT-3	Kelvin Chip Tweezers for 2150, 2160, 3525. 3550; 3'	SR	
SKP-8	Small Kelvin Probes for R1L-E2A, Spear Tips	SR	
SKP-8F	Small Kelvin Probes for R1L-E2A, Flat Tips	SR	
SKT/1750-5	Kelvin Chip Tweezers for 1740, 1750; 5'	SR	
SKT/252-5	Kelvin Chip Tweezers for 252, 253; 5'	SR	
ST-200A	AC Ratio Standard, 1:1 Ratio, Binding Post Termination, Center-Tapped Secondary (not CE certified)	N	
ST-248A	AC Ratio Standard, 1:1 Ratio, Binding Post Termination, Electrostatic Shields (not CE certified)	N	
TG-1500001-1	PMX & PS-Cal Commisioning, on site, within 250 miles of 44041	N	
TG-1500001-2	PMX & PS-Cal Commisioning, Remote over MS Teams	N	
TG-1500001-3	PMX & PS-Cal Commisioning, on site, within USA	N	

SR=Service
Replacement

Service Replacement indicates the product will be available as part of the support plan for EOL products