

SL POWER NGB250 SERIES

250 Watts Single Output
Medical & Industrial Grade



Medical



Industrial



LED/AV

Advanced Energy's SL Power NGB250 medically-approved AC-DC power supplies are available with a nominal main output of 12 V, 15 V, 19 V, 24 V, 28 V, 48 V or 56 V. NGB250 power supplies provide up to 250 Watts of output power with air flow. All models have output overvoltage, short circuit and overload protection and a 4 x 2 x 1.5 inch form factor.

AT A GLANCE

Total Power

250 Watts

Input Voltage

85 to 264 VAC

of Outputs

Single

SPECIAL FEATURES

- Up to 250 Watts with Air Flow
- Up to 175 Watts Convection Cooled
- 2"W x 4"L x 1.5"H Size
- Universal Input 85 to 264 VAC
- Meets Class B Emissions Levels
- 10+ Years Electrolytic Capacitor Life
- Meets Heavy Industrial/IEC60601-1-2 4th Edition EMC
- Less than 100 uA Leakage Current
- Class I and Class II Input Versions Available
- ROHS/REACH Compliant
- Covered Versions Available
- 3 Years Warranty

SAFETY

- c
- IEC/UL/EN62368-1



ELECTRICAL SPECIFICATIONS

Input	
Input range	85 to 264 VAC, 47 to 63 Hz, 1Ø
Input current	2.6 A max at 115 VAC, 1.3 A max at 230 VAC
Inrush current	75 A max., cold start @ 264 VAC input
Input fuses	6.3 A, 250 VAC fuse provided in both line & neutral
Leakage current	
Earth leakage current	<500 µA @ 264 VAC, 60 Hz, NC
Patient leakage current	<100/500 µA @ 264 VAC, 60 Hz, NC/SFC
Efficiency	>90% typical
No load input power	<0.5 W
Isolation voltage	Input/Ground: 2000 VAC (1 MOPP) Input/Output: 4400 VAC (2 MOPP) Output/Ground: 2000 VAC (1 MOPP)
Output	
Maximum power	See "Ordering information" section
Ripple and noise	1% of Vout on all models
Load regulation	2%
Line regulation	1%
Total regulation	5%
Minimum load	Not required
Capacitive load	1000 µF
Adjustment range	5%
Initial set point tolerance	±1 %
Overshoot	<3% overshoot at turn-on, <1% overshoot at turn-off, under all conditions
Monotonic waveform	PSU have monotonic wave forms on the main output at start up, shut down and fault (OVP, OCP, OTP, OPP, SCP) triggered shutdown.
Transient response	500 µs response time for return to within 0.5% of final value for any 50% load step over the range of 25% to 100% of rated load, $\Delta i/\Delta t < 0.2 \text{ A}/\mu\text{s}$. Max. voltage deviation is ±3.5% of final value.
Reliability	
MTBF	>500K hrs per Telcordia 332, Issue 6, 25°C, full rated load at 110 VAC input.
Warranty	3 years
Electrolytic capacitor lifetime	All specified electrolytic capacitors will exceed 10 year life based on operating at 25°C ambient temp., 24 hrs/day, 365 days/year.
Protection	
Overvoltage protection	115% to 155% of nominal output voltage. Requires AC recycle to reset.
Short circuit protection	Short across the output terminals will not cause damage to the unit. Hiccup mode.
Thermal protection	Will shutdown upon an over temperature condition. Auto-recovery mode.
Overload protection	130% to 180% of rated output current value. Hiccup mode.

DERATING SPECIFICATIONS

Ambient Temperature	12 V Model			15 V Model			24 V, 48 V & 56 V Models		
	100 to 265 VAC	90 VAC	80 VAC	100 to 265 VAC	90 VAC	80 VAC	100 to 265 VAC	90 VAC	80 VAC
50°C-Convection	145 W	135 W	120 W	155 W	145 W	125 W	175 W	165 W	145 W
50°C-w/Airflow	230 W	220 W	200 W	230 W	220 W	200 W	250 W	250 W	250 W
60°C-Convection	116 W	108 W	96 W	124 W	116 W	100 W	140 W	132 W	116 W
60°C-w/Airflow	184 W	176 W	160 W	184 W	176 W	160 W	200 W	200 W	200 W
70°C-Convection	87 W	81 W	72 W	93 W	87 W	75 W	105 W	99 W	87 W
70°C-w/Airflow	138 W	132 W	120 W	138 W	132 W	120 W	150 W	150 W	150 W
80°C-Convection	58 W	54 W	48 W	62 W	58 W	50 W	70 W	66 W	58 W
80°C-w/Airflow	92 W	88 W	80 W	92 W	88 W	80 W	100 W	100 W	100 W

EMI/EMC COMPLIANCE

Conducted emissions	EN55011/15/32: Class B, CISPR11/15/32: Class B, FCC Part 15.107, Class B, Measured at 10%, 50%, and 100% load steps; 6db margin typ, at 120 VAC and 230 VAC
Radiated emissions	EN55011/15/32: Class B, CISPR11/15/32: Class B, FCC Part 15.107, Class B, Measured at 10%, 50%, and 100% load steps; 3db margin typ, at 120 VAC and 230 VAC
Harmonic current emissions	EN61000-3-2, Class A at 230 VAC, 100% load
Voltage fluctuations & flicker	IEC61000-3-3
Electro static discharge immunity	EN55024/IEC61000-4-2, Level 4: ±8kV contact, ±15kV air, Criteria A, IEC60601-1-2, 4th Edition, Table 4
Radiated RF EM fields susceptibility	EN55022/EN61000-4-3, 10 V/m, 80 MHz to 2.7 GHz, 80% AM at 1 kHz IEC60601-1-2, 4th Edition, Table 4
Electrical fast transients / bursts	EN55024/IEC61000-4-4, Level 4, ±4 kV, 100 Khz rep rate, 40 A, Criteria A, IEC60601-1-2, 4th Edition, Table 5
Surges line to line (DM) and line to ground (CM)	EN55024/IEC61000-4-5, Level 4, ±2kV DM, ±4kV CM, Criteria A Surpasses IEC60601-1-2, 4th Edition requirements
Conducted disturbances induced by RF fields	EN55022/IEC61000-4-6, 3 V/m – Level 4, 0.15 to 80 MHz; and 12V/m in ISM and amateur radio bands between 0.15 MHz and 80 MHz, 80% AM at 1 KHz IEC60601-1-2, 4th Edition, Table 5
Rated power frequency magnetic fields test	EN55024/IEC1000-4-8, Level 4: 30 A/m, 50Hz/60Hz IEC60601-1-2, 4th Edition, Table 4
Voltage dips	EN55024/IEC/EN61000-4-11: --100% dip for 10 ms, at 0°, 45°, 90°, 135°, 180°, 225°, 270° and 315° --100% dip for 20 ms, 0°, criteria B --100% dip for 5000 ms (250/300 cycles), criteria B --60% dip for 100 ms, criteria B --30% dip for 500 ms, criteria A IEC60601-1-2, 4th Edition, Table 5
Common mode noise: high freq. (100 KHz to 20 MHz)	20 mA pk-pk

Notes:

Performance criteria are based on EN55024. According to the standards, performance criteria are decoded as following:

- A. Normal performance during and after the test
- B. Temporary degradation, self-recoverable
- C. Temporary degradation, operator intervention required to recover the operation
- D. Permanent damage

ORDERING INFORMATION

Model Number	Output Voltage	Output Current (fan)	Output Power (fan)	Output Current (convection / conduction)	Output Power (convection / conduction)	Terminations	
						Input	Output
NGB250S12K	12 V	19.1 A	230 W	12.1 A	145 W	3 pin (pin 2 removed) 0.156 Ctr Connector (Class I)	6 pin Header 0.156 Ctr Connector
NGB250S15K	15 V	15.3 A	230 W	10.3 A	155 W		
NGB250S24K	24 V	10.4 A	250 W	7.3 A	175 W		
NGB250S28K	28 V	8.9 A	250 W	6.2 A	175 W		
NGB250S48K	48 V	5.2 A	250 W	3.6 A	175 W		
NGB250S56K ¹	56 V	4.47 A	230 W	3.1 A	175 W		
NGB250S12C	12 V	19.1 A	230 W	12.1 A	145 W	3 pin (pin 2 removed) 0.156 Ctr Connector (Class II)	
NGB250S15C	15 V	15.3 A	230 W	10.3 A	155 W		
NGB250S19C	19 V	12.1 A	230 W	8.2 A	155 W		
NGB250S24C	24 V	10.4 A	250 W	7.3 A	175 W		
NGB250S48C	48 V	5.2 A	250 W	3.6 A	175 W		

Notes:

1. NGB250S56K is approved for IEC/UL/EN62368-1, not approved to IEC/UL/EN60601-1.
2. Covered versions available. Add "-C" to the end of the part numbers above. Airflow ratings derate by 20% with cover. Convection/Conduction ratings derate by 25% with cover.

ENVIRONMENTAL SPECIFICATIONS

Vibration	Random Vibration: Operating: 0.003 g/Hz, 1.5 grams overall, 3 axes, 10 min/axis, 5 to 500 Hz. Non-operating: Random waveform, 3 mins/axis, 3 axes and sine waveform, Vib. frequency / acceleration: 10 Hz to 500 Hz / 1 g, sweep rate of 1 octave/minutes, vibration time of 10 sweeps/axes, 3 axes. Transportation vibration: Random vib. per MIL-STD-810E, Method 514.4, Cat. 1, Figure 514.4-1, 1hr in each of three axes.
Shock	Operating: Half-sine, 20 gpk, 10 ms, 3 axes, 6 shocks total. Non-operating: Half-sine waveform, impact acceleration of 50 g, pulse duration of 6 ms. Number of shocks: 3 for each of the three axis
Cooling	Airflow: ≥300LFM. Convection.
Audible noise	<20 dbA
Operating temperature	-20°C to +80°C
Temperature derating	Derate output power linearly above 50°C to 40% Load at 80°C
Storage temperature	-40°C to +85°C
Altitude	Operating: -500 to 5,000 m. Non-operating: -500 to 12,192 m
Relative humidity	5% to 95%, non-condensing

SAFETY

UL	UL62368-1, UL60601-1-1, 3rd Edition + Am1. Complies with BF rated application requirements.
CSA	CAN/CSA-C22.2 No. 62368-1, 60601-1, BF Rated.
Demko	EN62368-1 EN60601-1-1, 3rd Edition + Am1. Complies with BF rated application requirements.
CB Report	Design to meet 5000 m and 50°C, 93% RH with 120 h (Tropical standard) according to GB4943 1-2011, IEC62368-1, IEC60601-1-1, complies with BF rated application requirements.

CONNECTORS

	Connector	Mating Connector
J1 (Input connector)	TE# 640445-3 (middle pin removed)	AMP P/N 640250-3. Pins: 640252-1
J3 (DC output connector)	TE# 640445-6	AMP P/N 640250-6. Pins: 640252-1
G1 (GND)	0.187 quick disconnect terminal	


UNIT PACKAGING REQUIREMENTS

Inserted instructions	Instruction sheet to be provided with all units packaged in individual unit box if used.
Individual unit packing	Units can be packed in egg crate type cartons for production quantities. Individual product shipments include an individual unit box.
Master carton shipping box	40 units per master carton. Unit packaged into carton must be protected such that it will sustain 1.4m drop test onto hard surface. Only anti-static packing material may be used inside the box. Exterior box sealing tape is anti-static type.
Individual carton packing box (when used)	Individual carton is labelled with ROHS sticker and individual label showing unit serial number, bar code, manufacturing date, bar code, and manufacturing part number, bar code, country of origin.

PIN ASSIGNMENTS

Connector	NGB250	
J1 (Input connector)	PIN 1	AC Neutral
	PIN 2	Empty
	PIN 3	AC Line
J3 (DC output connector)	PIN 1	RTN
	PIN 2	RTN
	PIN 3	RTN
	PIN 4	+Vo
	PIN 5	+Vo
	PIN 6	+Vo


MECHANICAL DRAWING



Notes:

1. All dimensions in mm (inches).
2. Dimensions: W: 2.13" x L: 4.06" x H: 1.5".
3. Unit weight: 290 g.

MECHANICAL DRAWING - COVERED VERSIONS



Notes:

1. All dimensions in mm (inches).
2. Dimensions: W: 2.46" x L: 4.30" x H: 1.5".
3. Unit weight: 300 g.



For international contact information,
visit advancedenergy.com.

powersales@aei.com (Sales Support)
productsupport.ep@aei.com (Technical Support)
+1 888 412 7832

ABOUT ADVANCED ENERGY

Advanced Energy (AE) has devoted more than four decades to perfecting power for its global customers. AE designs and manufactures highly engineered, precision power conversion, measurement and control solutions for mission-critical applications and processes.

Our products enable customer innovation in complex applications for a wide range of industries including semiconductor equipment, industrial, manufacturing, telecommunications, data center computing, and medical. With deep applications know-how and responsive service and support across the globe, we build collaborative partnerships to meet rapid technological developments, propel growth for our customers, and innovate the future of power.

PRECISION | POWER | PERFORMANCE | TRUST

Specifications are subject to change without notice. Not responsible for errors or omissions. ©2025 Advanced Energy Industries, Inc. All rights reserved. Advanced Energy®, and AE® are U.S. trademarks of Advanced Energy Industries, Inc.