



Product Service

CERTIFICATE

No. B 17 01 13890 02791

Holder of Certificate: **Astec International Ltd.**

16th Floor, Lu Plaza, 2 Wing Yip Street
Kwun Tong
Kowloon
HONG KONG



Certification Mark:



Product:

**Switching power supply unit
(Switching Power Supply for building-in)**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.: 682301700501

Valid until: 2019-06-19

Date, 2017-01-23

(Ricky Wang)

Page 1 of 2



**CERTIFICATE**

No. B 17 01 13890 02791

Model(s): CSU800AP-X-XXX
(Where "X" can be blank or any alphanumeric character, which is for marketing purpose only and have no impact on safety)

Parameters:

Rated input :	100-240VAC, 50/60Hz, 10A-5A or 240VDC, 4.5A max
Rated DC output :	12.0V, 66.7A MAX.; 12.0Vsb, 3.0A MAX. Total output power not to exceed 800W
Construction :	Built-in
Protection Class :	I
Degree of Protection :	IPX0

Remarks:

- When installing the equipments, all requirements of the mentioned standard must be fulfilled.
- The maximum operating temperature is 55°C.
- Clearance was evaluated for operating altitude up to 5000m above sea level.
- This power supply contains output exceeding 240VA, when installing into end system, care must be taken that the output and associated wire(s) should not be touched.
- Built-in type equipment, suitable enclosure should be provided by end system.

Tested according to: EN 60950-1:2006/A2:2013

Production Facility(ies): 41329