

Ref. Certif. No.

US-37273-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) **CB SCHEME CB TEST CERTIFICATE** Product POWER SUPPLY Name and address of the applicant SL POWER ELECTRONICS CORP BLDG A 6050 KING DR VENTURA CA 93003 UNITED STATES Name and address of the manufacturer SL POWER ELECTRONICS CORP BLDG A 6050 KING DR VENTURA CA 93003 UNITED STATES Name and address of the factory SL XIANGHE POWER ELECTRONICS CORP NO.B-02-03, NORTH SIDE OF LANDSCAPE AVE, QIBU Note: When more than one factory, please report on page 2 DISTRICT, ENVIRONMENTAL INDUSTRIAL PARK XIANGHE HEBEI 065400 CHINA Additional Information on page 2 Ratings and principal characteristics See Page 2 Trademark / Brand (if any) Type of Customer's Testing Facility (CTF) Stage used CTF Stage 3 SLB65SXXYZZ Model / Type Ref. See Page 2 Additional information (if necessary may also be reported on page 2) Additional Information on page 2 A sample of the product was tested and found IEC 62368-1:2014 to be in conformity with As shown in the Test Report Ref. No. which forms part E511363-A6013-CB-1 issued on 2020-12-24 of this Certificate This CB Test Certificate is issued by the National Certification Body UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

Date: 2020-12-25

Signature:

For full legal entity names see www.ul.com/ncbnames

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

Jolanta M. Wroblewska

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA



Ref. Certif. No.

US-37273-UL

Model Details:

SLB65SXXYZZ Where XX represents the output voltage which may be any number from 05 to 48. Y can be K (for Class I) ; ZZ can be any number between 00-99, blank or any letter from AA to ZZ, only for market purpose, not influence safety function.

Factories: INDUSTRIAS S L S A DE C V CIRCUITO SIGLO XXI 2055 COL PARQUE INDUSTRIAL EX-XXI 21254 MEXICALI BC MEXICO

Ratings: Input: 100-240Vac, 50-60Hz, 1.5A; Output: 5-48Vdc, 8-1.36A, 65W max.

Standard models output rating are listed as below: For SLB65S05YZZ: 5Vdc/8.0A, Max. 40W For SLB65S12YZZ: 12Vdc/5.0A, Max. 60W For SLB65S24YZZ: 24Vdc/2.71A, Max. 65W For SLB65S48YZZ: 48Vdc/1.36A, Max. 65W

Additional Information:

Additionally evaluated to EN 62368-1:2014/ A11:2017. National differences specified in the CB Test Report.

Additional information (if necessary)



UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Jolasha / hora Signature:

Jolanta M. Wroblewska

2/2

Date: 2020-12-25